


# Data Sheet

# Accessories



## E-Grip III Flooring Adhesive

E-Grip III is a zero-VOC, low odor, one-component urethane adhesive formulated specifically for use with Ecore's family of surfacing products. It features improved tack properties and has been specifically engineered to be solvent-free. With a moisture-cured, no-mix, non-sag and permanently elastic formula, it provides excellent adhesion to elastomers, concrete and wood in both indoor and outdoor applications.

### Advantages

- Zero-VOC formula (SCAQMD Rule #1168)<sup>1</sup>
- Solvent Free
- No mixing required
- Excellent curing cycle
- Very low odor
- Non-flammable
- Available in 4 gallon pails and 28 oz cartridges
- Meets Collaborative for High Performance Schools (CHPS) Low-Emitting Materials criteria (CA Section 01350)<sup>2</sup>
- Can contribute towards obtaining LEED credits

<b>Adhesive Type</b>	Single component polyurethane	<b>Maximum RH</b>	85% per ASTM F-2170
<b>Color</b>	Gray	<b>Freeze/Thaw Stability</b>	Stable
<b>Antimicrobial</b>	Yes	<b>Application Temp</b>	40°F to 100°F
<b>Adhesive Cure System</b>	Moisture-cured	<b>Flashpoint</b>	>500°F
<b>Voc Content</b>	0 lbs/gal (calculated)	<b>Shelf Life</b>	12 Months
<b>Solvents</b>	0 lbs/gal (calculated)	<b>Working Time</b>	30-40 Mins

## Trowel Size

<b>Trowel Size</b>	<b>Approximate Coverage</b>
1/16" x 1/32" x 1/32" U-notch	140 sq ft/gal
1/16" x 1/16" x 1/16" square notch	95 sq ft/gal
1/8" x 1/8" x 1/8" square notch	60 sq ft/gal

## Technical Data

For technical data, please visit [ecoreintl.com](http://ecoreintl.com)

## Health and Hazard Ratings

	<b>NFPA</b>	<b>HMIS</b>
<b>Health</b>	1	1
<b>Fire</b>	0	0
<b>Reactivity</b>	0	0
<b>Protective Equipment</b>	None	C

For handling and precautionary information, reference the product label and material safety data sheet.

<sup>1</sup> SCAQMD is the California "South Coast Air Quality Management District" Rule 1168 for adhesive flooring and sealant applications. The VOC content in E-Grip III complies with all adhesive applications listed by the SCAQMD.

<sup>2</sup> E-Grip III flooring adhesive meets the testing and product requirements of the California Department of Public Health (CDPH) Standard Method v. 1.1-2010 (Emissions Testing Method for CA Specification 01350).

All data statements and information presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, express warranty or merchantability or fitness for a particular purpose, or representation, express or implied, for which seller assumes legal responsibility, and they are offered solely for your consideration, investigation and verification.